

SPATHA
POWER TOOL



SPATHA
POWER TOOL

Taiwan Office : 8F.-5, NO.207,Dunhua N. Rd.,Songshen
Dist., Taipei City 105, Taiwan(R.O.C)

Tel : +886-2-2546-9636

Fax : +886-2-2546-9638

E-MAIL : info@mg-twt.com

China Office : Hengyuan Business BL,Tiantong Road(S),
Yinzhou,Ningbo,China,315100 ROOM 303

2019
CATALOG

2 Angle Grinder

4 Cut off Saw / Circular Saw /
Marble Cutter

6 Miter Saw / Band Saw / Table Saw

8 Rotary Hammer / Rotary Hammer Drill

10 Impact Drill / Electric Drill /
Demolition Hammer

12 Jig Saw / Rotary Hammer Drill

14 Electric Sander / Heat Gun /
Portable Blower



16 Cordless Drill /
Cordless Impact Driver



18 Cordless Multi Saw / Electric Mixer /
Electric Trimmer / Electric Router



20 Vibrator Motor / Die Grinder /
Mini Angle Grinder Set



22 Core Drill Maching / Impact Drill /
Core Drill Bit



24 Gasoline Engine



26 Gasoline Water Pump /
Gasoline Generator



28 Gasoline Generator / Diesel Generator



30 Diesel Generator




Angle Grinder 4
S-AG-600

Voltage	220V/50Hz
Power	600W
No-Load Speed	1100 r/min
Speed Round	100 mm
Cutting blade size	2 m
Weight	2.2 KGs


Angle Grinder 7
S-AG-2200

Voltage	220V/50Hz
Power	2200W
Empty rotation speed	8500 r/min
Diameter of Grinding Blades	180 mm
Weight	6 KGs

Angle Grinder	S-AG-750
Voltage	220V/50Hz
Power	750W
No-Load Speed	11000 r/min
Speed Round	100 mm
Cutting blade size	2 m


Angle Grinder
S-AG-900

Voltage	220V/50Hz
Power	900W
No-Load Speed	11000 r/min
Speed Round	100 mm
Cutting blade size	2 m




Cut off Saw
S-CF-335

Voltage	220-240V	Speed around	4000 r/min
Power	2100W	Cutting blade size	Ø 355 mm
Frequency	50/60 Hz	Weight	14.8 KGs


Circular Saw
S-CS-185

Voltage	220V	Speed around	5000 r/min
Power	1100W	Weight	4.1 KGs
Cutting blade size	Ø 185 mm		


Marble Cutter
S-MC-110

Voltage	220V	Speed around	13800 r/min
Power	1200W	Weight	3.5 KGs
Heels base diameter blades	4-3/8" (110mm)		


Circular Saw
S-CF-235

Voltage	220V	Speed around	5000 r/min
Power	2000W		
Cutting blade size	Ø 235 mm		


Band Saw
SA-BS-1100

Voltage	220V	No-load speed	0-2.4 r/min
Power	1100W	Cutting Capacity	127x127 mm
Blade Dimensions	1140x13x0.65 mm 14T	VDE plug	2 m
Blade FPM	0-420 f/min		


Miter Saw
SA-MS12-255

Motor	220V/50Hz / 1800W	Cutting Capacity 0°	89 mm
Blade dia	Ø 255 mm	Cutting Capacity 45° incline	67 mm
Speed around	5000 r/min	Weight	12 KGs
2m cable with VDE plug with single laser, with extension bar with wood clamp			


Table Saw
SA-TS254

Motor	220V/50Hz / 2000W	Cutting Capacity 90°	85 mm
Speed around	5000 r/min	Cutting Capacity 45°	60 mm
Right extension	25.4 inch	Weight	22 KGs
2m cable with VDE plug with aluminium main table			


Miter Saw
SA-MS19-255

Motor	220V/50Hz / 1800W	Cutting Capacity 0°	89 mm
Blade dia	Ø 255 mm	Cutting Capacity 45° incline	67 mm
Speed around	5000 r/min	Weight	19.5 KGs
2m cable with VDE plug with single laser, with extension bar with wood clamp			


Rotary Hammer
S-HD28-850

Voltage	220V/50Hz	Toolholder	SDS-Plus
Power	850W	Concrete	4-28 mm
Drill Bit	Ø 38 mm	Steel	13 mm
Speed Round	0-900 r/min	Wood	30 mm
Impact rate	0-5100BPM	Weight	2.8 KGs


Rotary Hammer Drill
S-HD20-650

Voltage	220V/50Hz	Toolholder	SDS-Plus
Power	850W	Concrete	4-28 mm
Drill Bit	Ø 38 mm	Steel	13 mm
Speed Round	0-1200 RPM	Wood	30 mm
Impact rate	0-5500 BPM	Weight	3.4 KGs


Rotary Hammer Drill
S-HD26-DFR

Voltage	220V/50Hz	Toolholder	SDS-Plus
Power	650W	Concrete	4-20 mm
Drill Bit	Ø 20 mm	Steel	13 mm
Speed Round	0-2100 RPM	Wood	30 mm
Impact rate	0-6100 BPM	Weight	2.5 KGs


Impact Drill
S-ID710

Voltage	220V
Power	550W
Speed Round	0-3000 r/min
Concrete	10 mm
Steel	13 mm
Wood	25 mm
Weight	1.7 KGs

Impact Drill
S-ID710

Voltage	220V/50Hz
Power	710W
Speed Round	0-3200 r/min
Steel	13 mm
Wood	16 mm
Weight	2.6 KGs


Electric Drill
S-ID710

Voltage	220V/50Hz
Power	710W
Speed Round	0-3200 r/min
Steel	13 mm
Wood	16 mm
Weight	2.6 KGs

Demolition Hammer
S-DH-5KG

Voltage	220V/50Hz
Power	1010W
Impact rate	2900 BPM
Impact energy	10
Weight	5.3 KGs


Demolition Hammer
S-DH-15KG

Voltage	220V/50Hz
Power	1750W
Impact rate	1380 BPM
Impact energy	45
Weight	15.1 KGs



Jig Saw S-JS-400

Voltage	220V50Hz
Power	400W
No load speed	500-3000RPM
Weight	1.8 KGs
• 3 Position pendulum	
• Variable 6-speed	


Rotary Hammer Drill S-RHD-32

Voltage	230-240V
Power	1250W
No load speed	2600 RPM
Impact energy	4.5J
Concrete	32 mm
Steel	13 mm
Wood	40 mm
Weight	5.2 KGs


Jig Saw S-JS-550

Voltage	220V50Hz
Power	650W
No load speed	0-3000RPM
Weight	1.8 KGs
• 3 Position pendulum	
• Variable 6-speed	


Rotary Hammer Drill S-RHD-28

Voltage	230-240V/50Hz
Power	1020W
No load speed	2850rpm
Impact energy	4.4J
Concrete	28 mm
Steel	13 mm
Wood	40 mm
Weight	5 KGs




Electric Sander
S-ES-90

Voltage	220V/50Hz	Oscillation	10000 r/min
Power	180W	Weight	1.7 KGs
Voltage	180x90 mm		
Sanding Pad	0-16000 r/min		

Heat Gun
S-HG-1800

Voltage	220V/50Hz
Power	1800W
Stage I Cool air	500 l/min
Stage II Cool air	300 l/min
Stage III Cool air	500 l/min
Oscillation	10000 r/min
Weight	2.2 KGs


Portable Blower
S-PB-600

Voltage	220V/50Hz
Power	600W
Air volume	0-4.1 m/s
Air Pressure	5.7 KPA
No Load Speed	0-16000 r/min
Weight	2.3 KGs




Cordless Drill
S-18CD-B

Voltage	18V	No Load Speed	0-350RPM / 0-1250RPM
Max Torque	25 N.M	Charing Time	1 hour
Adjustable Tourque	19+1	Weight	3.2 KGs
*2PC 1500mAh Battery Pack			


Cordless Drill
S-18CD-A

Voltage	18V	No Load Speed	0-350RPM / 0-1250RPM
Max Torque	35 N.M	Charing Time	1 hour
Adjustable Tourque	16	Weight	2.3 KGs
*2PC 1500mAh Battery Pack			


Cordless Drill
S-12CD-A

Voltage	12V	No Load Speed	0-350RPM / 0-1250RPM
Max Torque	26 N.M	Charing Time	1 hour
Adjustable Tourque	18+1	Weight	2.3 KGs
*2PC 1300mAh Battery Pack			


Cordless Impact Driver
S-12CID

Voltage	12V	No Load Speed	0-350RPM / 0-1250RPM
Max Torque	26 N.M	Charing Time	1 hour
Adjustable Tourque	18+1	Weight	2.54 KGs
*2PC 1300mAh Battery Pack			


Cordless Multi Saw S-12CMS

Voltage	12V
No Load Strokes	2200SPM
Steel	30mm
Wood	3mm
Charging Time	1 hour
Weight	3.6 KGs
* 2PC LI-ION 1300mAh Battery Pack	

Electric Trimmer
S-ET-530

Voltage	220V/50Hz
Power	530W
No Load Speed	35000 r/min
Drill Size	6mm (1/4")
Cable Length	2m
Weight	2.0 KGs


Electric Mixer
S-EM-1220

Voltage	220V/50Hz
Power	1220W
Mixing Paddle (max.)	Ø 140mm
Mixture Volume	120 Liters
Tool Fitting/Clamp Tread	M14 X 2
Weight	6.76 KGs


Electric Router
S-ER-2100

Voltage	220V/50Hz
Power	2100W
No Load Speed	9000-22000 r/min
Stroke Capacity	0-75mm
Big Ais	12mm (1/2")
Base Diameter	170mm
Cable Length	2m
Weight	7.0 KGs


Electric Mixer
S-EM-850

Voltage	220V/50Hz
Power	850W
Mixing Paddle (max.)	120mm
Mixture Volume	80 Liters
Tool Fitting/Clamp Tread	M14 X 2
Weight	4.5 KGs



Vibrator Motor
S-VM-900

Voltage	220V/50Hz
Power	900W
No Load Speed	5000RPM
Weight	2.15 KGs


Die Grinder
S-DG-750

Voltage	220V/50Hz
Power	750W
No Load Speed	28000 r/min
Collet Size	6 mm
Cable Length	2 m
Weight	1.8 KGs


Mini Angle Grinder Set
S-MAG-135

Voltage	220V/50Hz
Power	135W
No Load Speed	10000-32000BPM



Core Drill Machine
S-CDM-2500

Voltage	220V/50Hz
Power	2500W
No Load Speed	0-2200 RPM
Collet Size	180 mm
Weight	24 KGs


Impact Drill
S-CDM-3900

Voltage	220V/50Hz
Power	3900W
No Load Speed	0-600 RPM
Concrete	205 mm
Brick	260 mm
Weight	14 KGs


Core Drill Machine
S-CDM-1750

Voltage	220V/50Hz
Power	1750W
No Load Speed	0-2200 RPM
Collet Size	150 mm
Weight	3.25 KGs


Core Drill Bit
LASER WELDING

CDB-2	core bit tube Size: 2"	CDB-6	core bit tube Size: 6"
CDB-3	core bit tube Size: 3"	CDB-7	core bit tube Size: 7"
CDB-4	core bit tube Size: 4"	CDB-8	core bit tube Size: 8"
CDB-5	core bit tube Size: 5"		


Gasoline Engine
SA-168FA

Bore x Stroke	68x45 mm	Max.Torque	9/2500 (N.m/rpm)
Displacement	163 ml	Fuel Tank Capacity	3.6(L)
Compression Ratio	8.5:1	Oil capacity	0.6(L)
Max.Power Output	5.5(4.1)/3600 Hp(kw)/RPM	Min Fuel Consumption	395(g/kw.h)

Starting System: Recoil start/Electric start


Gasoline Engine
SA-170F

Bore x Stroke	70x54 mm	Max.Torque	9/2500 (N.m/rpm)
Displacement	163 ml	Fuel Tank Capacity	3.6(L)
Compression Ratio	8.5:1	Oil capacity	0.6(L)
Max.Power Output	5.5(4.1)/3600 Hp(kw)/RPM	Min Fuel Consumption	395(g/kw.h)

Starting System: Recoil start/Electric start


Gasoline Engine
SA-177F

Bore x Stroke	68x45 mm	Max.Torque	9/2500 (N.m/rpm)
Displacement	163 ml	Fuel Tank Capacity	3.6(L)
Compression Ratio	8.5:1	Oil capacity	0.6(L)
Max.Power Output	5.5(4.1)/3600 Hp(kw)/RPM	Min Fuel Consumption	395(g/kw.h)

Starting System: Recoil start/Electric start

Gasoline Water Pump
SA-WP20

Outlet Size(mm)	50 (2")
Displacement Q.max	32
Suction	7
Lift H.max	28
Weight	25 KGs


Gasoline Water Pump
SA-WP30

Outlet Size(mm)	80 (2")
Displacement Q.max	30
Suction	7
Lift H.max	50
Weight	26 KGs

SPATHA
 POWER TOOLS

**GASOLINE
 WATER
 PUMP**

Gasoline Generator
SA-G2500

Rated A.C. Output	2.0 kw
Max A.C. Output	2.5 kw
A.C. Frequency	50Hz
Voltage	220V
Engine Type	
Air-cooled ; 4Stroke; OHV, Single Cylinder Starting System	
Weight	41 KGs


Gasoline Generator
SA-G3500

Rated A.C. Output	2.5 kw
Max A.C. Output	2.8 kw
A.C. Frequency	50Hz
Voltage	220V
Engine Type	
Air-cooled ; 4Stroke; OHV, Single Cylinder Starting System	
Weight	43 KGs

Gasoline Generator
SA-G6500

Rated A.C. Output	5.0 kw
Max A.C. Output	5.5 kw
A.C. Frequency	50Hz
Voltage	220V
Engine Type	
Air-cooled ; 4Stroke; OHV, Single Cylinder Starting System	
Weight	82 KGs




Gasoline Generator
SA-G3500A

Rated A.C. Output 2.0 kw

Max A.C. Output 2.2 kw

A.C. Frequency 50Hz

Voltage 220V

Engine Type

Air-cooled ; 4Stroke; OHV, Single Cylinder Starting System

Weight 41.5 KGs


Diesel Generator
SA-DG-6500

Rated A.C. Output 4.5kw Displacement 418cc

Max A.C. Output 5.0kw Noise Level 75-79 dB

A.C. Frequency 50/60Hz Low Oil Pressure Alert System

Rate Voltage 220/110V Electric Start with 30AH Battery

Engine Type Air-cooled; 4Stroke; OHV, Single Cylinder Starting System

Gasoline Generator
SA-G3500B

Rated A.C. Output 2.5 kw

Max A.C. Output 2.8 kw

A.C. Frequency 50Hz

Voltage 220V

Engine Type

Air-cooled ; 4Stroke; OHV, Single Cylinder Starting System

Weight 42.5 KGs


Gasoline Generator
SA-G6500C

Rated A.C. Output 5.0 kw

Max A.C. Output 5.5 kw

A.C. Frequency 50Hz

Voltage 220V

Engine Type

Air-cooled ; 4Stroke; OHV, Single Cylinder Starting System

Weight 87 KGs


Diesel Generator
SA-DG-6500X

Rated A.C. Output 4.5kw Output Current Range 50-180 Amp

Max A.C. Output 5.0kw Continuous Running Time 8.5H

A.C. Frequency 50/60Hz Low Oil Pressure Alert System

Rate Voltage 220/110V Electric Start with 30AH Battery

Engine Type Air-cooled; 4Stroke; OHV, Single Cylinder Starting System


Diesel Generator
SA-DG-6500LN

Rated A.C. Output	4.5kw	Displacement	418cc
Max A.C. Output	5.0kw	Noise Level	72 dB
A.C. Frequency	50/60Hz	Low Oil Pressure Alert System	
Rate Voltage	220/110V	Electric Start with 30AH Battery	
Engine Type Air-cooled; 4Stroke; OHV, Single Cylinder Starting System			


Diesel Generator
SA-WP30D

Outlet Size(mm)	80 (2")	Lift H.max	30
Displacement Q.max	13	Weight	44 KGs
Suction	7		

